




Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth, PL6 7TL, England.
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724
 and at 1, Enterprise Close, Factory Lane, Croydon, CR0 3RZ
 Telephone 020 8665 8100 Fax 0208 8665 8100
 Website: <http://www.birchvalley.co.uk> E mail: info@birchvalley.co.uk



POLYESTER BRAIDED SLEEVING

This expandable sleeving is manufactured from monofilaments of polyester giving a very abrasion resistant covering for single or multi-core cables. Each size covers a wide range of cable bundles as it expands from its supplied size and then recovers.

MATERIAL CHARACTERISTICS

| | |
|--------------------------|--------------------------------------|
| Continuous temperature | -50 to 150 C |
| Intermittent temperature | 220 C |
| Monofilament | 0.22 mm |
| Melting point | 250 C |
| Limiting oxygen index | 34 % |
| Flame resistance | meets UL94 - V2 |
| Fumes toxicity | passes CEI 754-1 & 2 halogen free |
| Fume opacity | passes |
| Flammability | passes |

TEST METHODS

NFG 07-128

NFC 20452 (polymer)
 CEI 332-1& FMVSS 302
 (Type A) I2 according to
 NFF16-101

RoHS compliant yes

| Part no. | Recommended range mm | Coil size m | Reel size m |
|----------|----------------------|-------------|-------------|
| PB/PG 03 | 1 to 5 | 100 | 1000 |
| PB/PG 04 | 2 to 7 | 100 | 1000 |
| PB/PG 05 | 3 to 9 | 100 | 400 |
| PB/PG 06 | 4 to 11 | 100 | 400 |
| PB/PG 08 | 5 to 13 | 100 | 300 |
| PB/PG 10 | 7 to 15 | 100 | 300 |
| PB/PG 12 | 8 to 17 | 50 | 300 |
| PB/PG 15 | 10 to 20 | 50 | 300 |
| PB/PG 20 | 14 to 26 | 25 | 200 |
| PB/PG 25 | 18 to 34 | 25 | 200 |
| PB/PG 30 | 20 to 40 | 25 | 150 |
| PB/PG 40 | 30 to 50 | 25 | 100 |
| PB/PG 50 | 40 to 66 | 25 | 100 |

All sizes available in ready cut lengths.

Standard colours PB - black, PG - grey

