



Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth, PL6 7TL, England.  
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724  
 and at 1, Enterprise Close, Factory Lane, Croydon, CR0 3RZ  
 Telephone 020 8665 8100 Fax 0208 8665 8100  
 Website: <http://www.birchvalley.co.uk> E mail: [info@birchvalley.co.uk](mailto:info@birchvalley.co.uk)



## ACRYLIC GLASS SLEEVING VIDAFLEX 942

*Vidaflex 942 AGS is tough flexible insulating sleeving based on a close braided E type glass yarn coated with acrylic resin together giving a high quality product performing under exacting standards. Widely used in class F motors, transformers and where coolants FREON 12 and 22 are used.*

### MATERIAL CHARACTERISTICS

Continuous temperature	-25 to 155 C
Intermittent temperature	200 C
Dielectric strength	2.5 kV
Resistance to flam	longer than 45 seconds for 25mm
Copper corrosion	nil
Resistance to fungus	inert
Resistance to chemicals	
acids, alkalis	excellent
organic solvents	swells but does not separate
Specification	IEC 684-3 403/405
RoHS compliant	Yes

Part no.	Nominal inside dia. mm	Nominal wall mm (min)	Coil size m
AGS 1	1.0	0.35	500
AGS 1.5	1.5	0.35	500
AGS 2	2.0	0.35	250
AGS 3	3.0	0.45	250
AGS 4	4.0	0.45	100
AGS 5	5.0	0.5	100
AGS 6	6.0	0.5	100
AGS 8	8.0	0.65	100
AGS 10	10.0	0.65	50
AGS 12	12.0	0.63 - 0.71	50
AGS 14	14.0	0.67 - 0.71	50
AGS 16	16.0	0.71 - 0.73	50
AGS 20	20.0	0.92 - 1.02	50

All sizes available in cut lengths.

Standard colours - black and yellow to size 12  
 black only 14mm and above