



Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth, PL6 7TL, England.
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724
 and at 1, Enterprise Close, Factory Lane, Croydon, CRO 3RZ
 Telephone 020 8665 8100 Fax 0208 8665 8100
 Website: <http://www.birchvalley.co.uk> E mail: info@birchvalley.co.uk



HEAT TREATED BRAIDED GLASS GLASS SLEEVING VIDAFLEX L124

Vidaflex L 124 HTG is an uncoated heat treated glass yarn which has an operating temperature of 200C but will withstand short term operation up to 600C. Suitable for use in high temperature applications and as reinforcement and heat protection on cables.

MATERIAL CHARACTERISTICS

Continuous temperature	25 to 220 C
Intermittent temperature	600 C
Melt temperature	700 C
Thermal Classification	Class C 220 C
RoHS compliant	Yes

Part no.	Nominal inside dia. mm	Nominal wall mm (min)	Coil size m
HTG 4	4.0	0.35 - 0.7	100
HTG 5	5.0	0.35 - 0.7	100
HTG 6	6.0	0.35 - 0.7	100
HTG 8	8.0	0.35 - 0.7	100
HTG 10	10.0	0.35 - 0.7	50
HTG 12	12.0	0.35 - 0.7	50
HTG 14	14.0	0.35 - 0.7	50
HTG 16	16.0	0.35 - 0.7	50
HTG 20	20.0	0.35 - 0.7	50

All sizes available in cut lengths.

Standard colour - natural

Smaller sizes may be avails to special order