



Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth, PL6 7TL, England.
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724
 and at 1, Enterprise Close, Factory Lane, Croydon, CR0 3RZ
 Telephone 020 8665 8100 Fax 0208 8665 8100
 Website: <http://www.birchvalley.co.uk> E mail: info@birchvalley.co.uk



SILICONE COATED GLASS SLEEVING
UL APPROVED VIDAFLEX S550

A close braided sleeving which is coated with silicone rubber giving good dielectric strength and moisture resistance. SRGU is the same as SRG but has UL approval to 600V.

MATERIAL CHARACTERISTICS

Continuous temperature	-60 to 180 C
Intermittent temperature	250 C
Dielectric strength	4.0 kV
Thermal Classification	Class H 180C
Flammability	Self extinguishing
Specifications	IEC 684-3-402 ASTM D-372 Type 5 NEMA VS-1 Grade C1 UL rating 600V
Rohs compliant	yes

Part no.	Nominal inside dia. mm	Nominal wall mm (min)	Reel size m
SRGU 1	1.0	0.8	250
SRGU 1.5	1.5	0.8	250
SRGU 2	2.0	0.8	250
SRGU 2.5	2.5	0.8	250
SRGU 3	3.0	0.8	250
SRGU 3.5	3.5	0.8	250
SRGU 4	4.0	0.8	100
SRGU 5	5.0	0.8	100
SRGU 6	6.0	0.8	100
SRGU 7	7.0	0.8	100
SRGU 8	8.0	0.8	100
SRGU 10	10.0	0.9	50
SRGU 12	12.0	0.9	50
SRGU 16	16.0	0.9	50
SRGU 20	20.0	0.9	50

Standard colour - black

Also available in knitted version, S350, but minimum quantities will apply.