



Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth, PL6 7TL, England.
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724
 and at 1, Enterprise Close, Factory Lane, Croydon, CR0 3RZ
 Telephone 020 8665 8100 Fax 0208 8665 8100
 Website: <http://www.birchvalley.co.uk> E mail: info@birchvalley.co.uk



SILICONE COATED GLASS SLEEVING VIDAFLEX SD550

A close braided sleeving which is coated with silicone rubber giving good dielectric strength and moisture resistance. SRG is extremely flexible and has good resistance to transformer oils, weak acids, liquid fuels, water etc. Suitable for Class H & C applications up to 220C.

MATERIAL CHARACTERISTICS

Continuous temperature	-60 to 180 C
Intermittent temperature	250 C
Dielectric strength	4.0 kV
Thermal Classification	Class H 180C
Flammability	Self extinguishing
Specifications	IEC 684-3-402 ASTM D-372 Type 5 NEMA VS-1 Grade C1
Rohs compliant	yes

Part no.	Nominal inside dia. mm	Nominal wall mm (min)	Reel size m
SRG 1	1.0	0.6	250
SRG 1.5	1.5	0.6	250
SRG 2	2.0	0.6	250
SRG 2.5	2.5	0.6	250
SRG 3	3.0	0.6	250
SRG 3.5	3.5	0.6	250
SRG 4	4.0	0.6	100
SRG 5	5.0	0.6	100
SRG 6	6.0	0.6	100
SRG 7	7.0	0.6	100
SRG 8	8.0	0.8	100
SRG 10	10.0	0.8	50
SRG 12	12.0	0.8	50
SRG 16	16.0	0.8	50
SRG 20	20.0	0.8	50

All sizes available in cut lengths.

Standard colour – black

Also available in knitted form, SD350 but minimum quantities will apply.