



POLYESTER BRAIDED SLEEVING

This expandable sleeving is manufactured from monofilaments of polyester giving a very abrasion resistant covering for single or multi-core cables. Each size covers a wide range of cable bundles as it expands from its supplied size and then recovers.

MATERIAL CHARACTERISTICS

Continuous temperature	-50 to 150 °C
Intermittent temperature	220 °C
Monofilament	0.22 mm
Melting point	250 C
Limiting oxygen index	34 %
Flame resistance	meets UL94 - V2
Fumes toxicity	passes CEI 754-1 & 2 halogen free
Fume opacity	passes NFC 20452 (polymer)
Flammability	passes CEI 332-1& FMVSS 302 Type A I2 according to NFF16-101
RoHS compliant	yes

Part no.	Recommended range mm	Coil size m	Reel size m
PB/PG 03	1 to 5	100	1000
PB/PG 04	2 to 7	100	1000
PB/PG 05	3 to 9	100	400
PB/PG 06	4 to 11	100	400
PB/PG 08	5 to 13	100	300
PB/PG 10	7 to 15	100	300
PB/PG 12	8 to 17	50	300
PB/PG 15	10 to 20	50	300
PB/PG 20	14 to 26	25	200
PB/PG 25	18 to 34	25	200
PB/PG 30	20 to 40	25	150
PB/PG 40	30 to 50	25	100
PB/PG 50	40 to 66	25	100

All sizes available in ready cut lengths.

Standard colours PB - black, PG - grey

Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth PL6 7TL, England
Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724