



SILICONE COATED GLASS SLEEVING
UL APPROVED VIDAFLEX S350

A close knitted sleeving which is coated with silicone rubber giving good dielectric strength and moisture resistance. SRGU350 is the same as SRG350 but has UL approval..

MATERIAL CHARACTERISTICS

Continuous temperature	-60 to 180 C
Intermittent temperature	250 C
Breakthrough Voltage at RT (kV)	7.0 kV
Thermal Classification	Class H 180C
Flammability	Self extinguishing
Specifications	UL file E154100(M)
Rohs compliant	yes

Part no.	Nominal inside dia. mm	Nominal wall mm (min)	Reel size m
SRG350 U 3	3.0 +/- 0.15	1.0	250
SRG350 U 4	4.0 +/- 0.2	1.0	100
SRG350 U 5	5.0 +/- 0.2	1.0	100
SRG350 U 6	6.0 +/- 0.25	1.0	100
SRG350 U 7	7.0 +/- 0.25	1.0	100
SRG350 U 8	8.0 +/- 0.25	1.0	100
SRG350 U 9	9.0 +/- 0.3	1.0	100
SRG350 U 10	10.0 +/- 0.3	1.0	100
SRG350 U 12	12.0 +/- 0.3	1.0	100
SRG350 U 16	16.0 +/- 0.4	1.0	50
SRG350 U 20	20.0 +/- 0.5	1.0	50
SRG350U 25	25.0 +/- 0.5	1.4	25

Standard colours – black and red/oxide

Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth PL6 7TL, England
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724

1 Enterprise Close, Factory Lane, Croydon CR0 3RZ, England
 Telephone: +44 (0)20 8665 8100 Fax: +44 (0)208 8665 8101

Website: www.birchvalley.co.uk Email: info@birchvalley.co.uk