



**SILICONE COATED GLASS SLEEVING**  
**UL APPROVED VIDAFLEX S550**

*A close braided sleeving which is coated with silicone rubber giving good dielectric strength and moisture resistance. SRGU is the same as SRG but has UL approval to 600V.*

**MATERIAL CHARACTERISTICS**

Continuous temperature	-60 to 180 °C
Intermittent temperature	250 C
Dielectric strength	4.0 kV
Thermal Classification	Class H 180°C
Flammability	Self extinguishing
Specifications	IEC 684-3-402 ASTM D-372 Type 5 NEMA VS-1 Grade C1 UL rating 600V
Rohs compliant	yes

Part no.	Nominal inside dia. mm	Nominal wall mm (min)	Reel size m
SRGU 1	1.0	0.8	250
SRGU 2	2.0	0.8	250
SRGU 2.5	2.5	0.8	250
SRGU 3	3.0	0.8	250
SRGU 4	4.0	0.8	100
SRGU 5	5.0	0.8	100
SRGU 6	6.0	0.8	100
SRGU 7	7.0	0.8	100
SRGU 8	8.0	0.8	100
SRG 9	9.0	0.8	100
SRGU 10	10.0	0.9	50
SRGU 12	12.0	0.9	50
SRGU 16	16.0	0.9	50
SRGU 20	20.0	0.9	50

Standard colours – black and red/oxide

Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth PL6 7TL, England  
 Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724

1 Enterprise Close, Factory Lane, Croydon CR0 3RZ, England  
 Telephone: +44 (0)20 8665 8100 Fax: +44 (0)208 8665 8101

Website: [www.birchvalley.co.uk](http://www.birchvalley.co.uk) Email: [info@birchvalley.co.uk](mailto:info@birchvalley.co.uk)