



GREEN/YELLOW P.V.C EARTH SLEEVING

A general purpose P.V.C. supplied with green and yellow stripes for use in earth identification. In addition to direct use this sleeving is widely sold in the distribution market and for electrical contracting purpose.

MATERIAL CHARACTERISTICS

Continuous temperature	-20 to 70 C
Insulation resistance	10 ¹⁰ Ohm/cm
Dielectric strength	20 kV/mm
Tensile strength	15 MPa
Elongation at break	220%
Hardness	BSS20-30
Flammability	self extinguishing in 30 seconds
RoHS compliant	yes

Part no.	Inside dia. mm	Nominal wall mm	Coil size m
GY 1.5	1.5	0.4	100
GY 2	2.0	0.4	100
GY 3	3.0	0.4	100
GY 4	4.0	0.4	100
GY 5	5.0	0.45	100
GY 6	6.0	0.45	100
GY 8	8.0	0.45	100
GY 10	10.0	0.45	100
GY 12	12.0	0.45	100
GY 14	14.0	0.45	100
GY 16	16.0	0.45	100
GY 18	18.0	0.45	100
GY 19	19.0	0.45	100
GY 20	20.0	0.45	100
GY 25	25.0	0.45	100

Can be supplied on reels to special order

Standard colour -green/yellow only.

Larger sizes may be subject to minimum quantities.

Birch Valley Plastics Ltd, Darklake View, Estover, Plymouth PL6 7TL, England
Telephone: +44 (0)1752 696515 Fax: +44 (0)1752 696724